

2020 MODEL LINEUP		Sport Boats			Sport Decks				Deck Boats				Cuddies / Cruisers			Center Consoles				Dual Consoles				
		225	225	250	198	204	214	208	215	235	182	192	201	212	208	225	250	186	206	216	236	191	231	269
Engine Type		IO	IO	IO	IO	O/B	O/B	O/B	IO	O/B	O/B	O/B	O/B	CR	CR	CR	O/B	O/B	O/B	O/B	O/B	O/B	O/B	
Length Overall	ft	22'11"	22'11"	25'0"	19'9"	20'5"	21'6"	20'8"	21'11"	23'11"	19'1"	20'1"	20'1"	21'11"	20'6"	22'11"	25'0"	19'11"	20'11"	21'8"	23'9"	19'1"	23'8"	27'6"
	m	7.0	7.0	7.6	6.0	6.2	6.6	6.3	6.7	7.3	5.8	6.1	6.1	6.7	6.3	7.0	7.6	5.8	6.1	6.6	7.2	5.8	7.2	8.4
Beam	in	100.0	100.0	102	94.0	98.5	101.0	98.5	101.0	101.0	90.0	100.0	100.0	102.0	98.5	100	102	90.0	100.0	101.0	101.0	90.0	101.0	102.0
	cm	254.0	254.0	259	238.8	250.2	256.5	250.2	256.5	256.5	228.6	254.0	254.0	259.1	250.2	254	259	228.6	254.0	256.5	256.5	228.6	256.5	259.1
Bridge Clearance (With Standard Windshield)	in	52.0	52.0	65	47.0	49.0	58.0	49.0	58.0	58.0	39.0	50.0	60.0	50.0	49.0	55	65	59.0	63 (73)	72.0	72.0	50.5	58.0	
	cm	132.1	132.1	165	119.4	124.5	147.3	124.5	147.3	147.3	99.1	127.0	152.4	127.0	124.5	140	165	149.9	160 (186)	182.9	182.9	128.3	147.3	
Bridge Clearance (With Factory T Top)	in																			96.0	96.0	96.0		
	cm																			243.8	243.8	243.8		
Average Dry Weight (w/ popular engine)	lb	3364	3364	4340	2828	2490	3114	2974	3705	4105	2000	2600	2800	3100	3074	3539	4192	2300	2700	3150	3648	2000	3648	5500
	kg	240HP	240HP	240HP	200HP	115HP	150HP	200HP	240HP	240HP	30HP	115HP	115HP	150HP	200HP	240HP	240HP	115HP	140HP	200HP	250HP	30HP	250HP	250HP
Fuel Capacity	gal	59	59	68	34	34	46	34	46	34	46	21	46	46	57	34	55	68	34	46	57	68	21	56
	liter	212	212	257	129	129	174	129	174	129	174	79	174	174	216	129	212	257	129	174	216	257	79	212
Water Capacity	gal	6	6	13	6	6	13	6	13	13	6	13	13	13	6	6	13	13	6	13	13	6	13	20
	liter	23	23	49	23	23	49	23	49	49	23	49	49	49	23	23	49	49	23	49	49	23	49	76
Ice Box / Cooler Capacity	qt	32+25	32+25	32+32+25	32+14	32+14	25+17	32+14	25+17	25+32	25+22	67+25+45	67+25+45	67+25+45	25	25	32+25	48+68	48+68	74+68	74+68	25+22	25+32	#VALUE!
	liter	30+24	30+24	30+30+24	30+13	30+13	24+16	30+13	24+16	24+30	24+21	63+24+43	63+24+43	63+24+43	+24	+24	30+24	45+64	45+64	70+64	70+64	24+21	24+30	#VALUE!
Livewell Capacity	gal				11	11	11	11	11	11	6	11	11	11				26+17	26+17	14+17	14+17	6	11	
	liter				42	42	42	42	42	42	23	42	42	42				98+64	98+64	53+64	53+64	23	42	
Max Capacity	ppl/lb	10/2080	10/2080	10/2265	9/1450	9/1715	11/2167	9/1715	11/2167	12/2535	9/2025	10/2225	10/2225	12/2600	9/1715	10/2080	10/2265	7/1875	9/2400	10/3050	12/3250	9/2025	12/2535	#VALUE!
	ppl/kg	10/943	10/943	10/1027	9/657	9/778	11/983	9/778	11/983	12/1150	9/918	10/1009	10/1009	12/1179	9/778	10/943	10/1027	7/850	9/1088	10/1383	12/1474	9/918	12/1150	#VALUE!
Max Engine Power	hp				150	225					115	175	175	200				150	200	200	300	115	300	425
Molded Depth (Windshield Base to Keel)	in	51.0	51.0	66	47.0	48.0	58.0	48.0	58.0	58.0	46.0	55.0	55.0	55.0	51.0	54	66	59.0	62.0	68.0	68.0	55.0	58.0	
	cm	129.5	129.5	168	119.4	121.9	147.3	121.9	147.3	147.3	116.8	139.7	139.7	139.7	129.5	137	168	149.9	157.5	172.7	172.7	139.7	147.3	
Max Depth (With Standard Windshield)	in	58.0	58.0	77	59.0	62.0	72.0	62.0	72.0	72.0	48.0	63.0	63.0	63.0	61.0	61	77	71.0	74.0	85.0	85.0	61.0	61.0	
	cm	147.3	147.3	196	149.9	157.5	182.9	157.5	182.9	182.9	121.9	160.0	160.0	160.0	162.6	155	196	180.3	188.0	215.9	215.9	154.9	182.9	
Max Draft (Drive Down)	in	33.0	33.0	34	32.0	31.0	32.0	34.0	34.0	34.0	28.0	31.5	31.5	31.5	34.0	33	34	28.0	31.0	32.0	33.0	28.0	32.0	
	cm	83.8	83.8	86	81.3	78.7	81.3	86.4	86.4	86.4	71.1	80.0	80.0	80.0	86.4	84	86	71.1	78.7	81.3	83.8	71.1	81.3	
Max Draft ^ (Drive Up)	in	18.0	18.0	17	18.0	18.0	17.0	18.0	17.0	17.0	12.5	14.5	14.5	14.0	18.0	16	17	12.5	14.0	15.0	16.0	12.5	17.0	
	cm	45.7	45.7	43	45.7	45.7	43.2	45.7	43.2	43.2	31.8	36.8	36.8	35.6	45.7	46	43	31.8	35.6	38.1	40.6	31.8	43.2	
Bow Depth (Bow to Cushion Top)	in	20.0	20.0	17	15.0	16.0	17.0	16.0	17.0	17.0	11.5	10.0	14.0	10.0	27.0	28	32	NA	9.5	10.0	10.0	11.5	17.0	
	cm	50.8	50.8	43	38.1	40.6	43.2	40.6	43.2	43.2	29.2	25.4	35.6	25.4	68.6	71	81	NA	24.1	25.4	25.4	29.2	43.2	
Bow Depth (Max Depth)	in	34.0	34.0	39	32.0	31.5	33.0	31.5	33.0	33.0	26.4	26.2	30.0	26.4	45.0	49	58	21.5	23.3	24.0	24.0	26.4	33.0	
	cm	86.4	86.4	99	81.3	80.0	83.8	80.0	83.8	83.8	67.1	66.6	76.2	67.1	114.3	124	147	54.6	59.2	61.0	61.0	67.1	83.8	
Bow Length (Max Length)	in	59.0	59.0	68	55.2	55.2	59.0	55.2	59.0	59.0	65.0	65.0	65.0	65.0	66.0	81	68	55.0	60.0	73.0	73.0	65.0	59.0	
	cm	149.9	149.9	173	140.2	140.2	149.9	140.2	149.9	149.9	165.1	165.1	165.1	165.1	167.6	206	173	139.7	152.4	185.4	185.4	165.1	149.9	
Cockpit Depth (At Helm)	in	33.0	33.0	36	31.0	31.8	34.0	31.8	34.0	34.0	27.0	27.5	32.0	27.5	34.0	36	36	23.0	24.5	24.5	24.5	29.5	34.0	
	cm	83.8	83.8	91	78.7	80.8	86.4	80.8	86.4	86.4	68.6	69.9	81.3	69.9	86.4	91	91	58.4	62.2	62.2	62.2	74.9	86.4	
Cockpit Width (Max Molded)	in	81.0	81.0	79	77.0	81.0	81.0	81.0	81.0	81.0	73.0	84.0	84.0	84.0	81.0	81	79	70.0	84.0	84.0	84.0	73.0	81.0	
	cm	205.7	205.7	201	195.6	205.7	205.7	205.7	205.7	205.7	185.4	213.4	213.4	213.4	205.7	206	201	177.8	213.4	213.4	213.4	185.4	205.7	
Cockpit Length (Max Molded)	in	103.0	103.0	119	99.0	101.0	107.0	101.0	107.0	120.0	160.0	156.0	166.5	178.0	85.0	94	119	170.0	188.0	192.0	208.0	104.3	120.0	
	cm	261.6	261.6	302	251.5	256.5	271.8	256.5	271.8	304.8	429.3	396.2	429.3	452.1	215.9	239	302	431.8	477.5	487.7	528.3	264.9	304.8	
Sleeping Capacity															2+1	2+1	2+2							
Deadrise	deg	20	20	21	19	20	21	20	21	21	19	20	20	20	20	20	21	19	20	21	21	19	21	21
Transom Angle	deg	15	15	15	15	15	13	15	15	15	15	13	13	13	15	15	15	15	15	15	15	15	15	15

Red Data Is Indicates Optional Equipment

*Weights vary depending on installed options. Refer to Performance Options for additional information.